

## POLYURETHANE TUBING



DATE  
: 07/08/2026 06:01 AM

SKU  
: 34

BRAND  
: DIXON VALVE

MODEL  
: 04063

Use:  
Designed for use with push-in fittings

Features:  
Excellent memory, flexibility and resistance to kinking  
Good resistance to fuels and oils  
Low gas and vapor permeability  
High compressive strength  
Low compressive set and extractability levels  
Outstanding abrasion resistance  
UV stabilized

Construction:  
Naturally transparent  
Glossy finish

Note:  
NSF61 certified for potable water

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	04063
<b>Material</b>	Polyurethane
<b>Temperature Range</b>	-40°F to 165°F (-40°C to 74°C)
<b>Tube ID</b>	.062"
<b>Tube OD</b>	1/8"
<b>Wall Thickness</b>	.0295
<b>Weight Lb</b>	0.3750
<b>Working Pressure</b>	255 PSI at 75°F (24°C)