


**DQC CVV-SERIES EUROPEAN
INTERCHANGE FEMALE
COUPLER**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 10:49 PM

SKU
: 379

BRAND
: DIXON VALVE

MODEL
: 10CVVF10

Construction:

Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Note:

Threaded sleeves enable easy connection and disconnection while system is under residual pressure only.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1-1/4"
Burst Pressure	17600 PSI (1200 Bar)
Factory Part Number	10CVVF10
Hex	50mm
Length	5.59" (142.0mm)
Material	Steel
Maximum OD	79.8mm

TECHNICAL SPECIFICATIONS

Maximum Operating Pressure	4400 PSI (300 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	1-1/4" - 11-1/2
Weight Lb	4.7600