

DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 04:51 AM

SKU

: 383

BRAND

: DIXON VALVE

MODEL

: 10EM10-B

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using solid brass

Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Steel sleeves are standard to maximize service life, hardened to resist deformation.

Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1-1/4"
Burst Pressure	6,800 PSI (469 Bar)
Factory Part Number	10EM10-B
Male Thread	NPTF
Male Thread Size	1-1/4" - 1-1/2"
Material	Brass
Maximum Operating Pressure	1,700 PSI (117 Bar)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	1.6700