


## WS-SERIES HIGH PRESSURE WINGSTYLE FEMALE COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 06:28 AM

SKU

: 22027

BRAND

: DIXON VALVE

MODEL

: 10WSF10-SS

Applications:

Used extensively in oil field and off shore oil rig applications

Construction:

Machined components are manufactured using solid 316 stainless steel bar stock.

Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Zinc Nickel for superior corrosion resistance.

Rugged high-strength steel wing nut for threaded connect and disconnect operation.

Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to +250°F (-40°C to +121°C)

PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.

Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

Compatibility & Interchange Data:

Snap-Tite 75-Series, Hydraulics Inc. Series- 5TV, DNP VFF-HD

Stucchi VOF, Faster OGV, Eaton FD85, Holmbury LC

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1-1/4"
<b>Burst Pressure</b>	15000 PSI (1000 bar)
<b>Factory Part Number</b>	10WSF10-SS
<b>Length</b>	4.40" (111.8mm)
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	4.65" (118.1mm)
<b>Maximum Operating Pressure</b>	3000 PSI (200 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1-1/4" - 11-1/2
<b>Weight Lb</b>	5.5500