


WS-SERIES HIGH PRESSURE WINGSTYLE CODE 62 FLANGE PAD COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 05:22 AM

SKU

: 22030

BRAND

: DIXON VALVE

MODEL

: 10WSFP10

Applications:

Used extensively in oil field and off shore oil rig applications

Features:

Interchanges with Snap-Tite 75 series

Contact Dixon ® for pressure ratings and other technical information

Construction:

Machined components are manufactured using solid steel bar stock.

Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Zinc Nickel for superior corrosion resistance.

Rugged high-strength steel wing nut for threaded connect and disconnect operation.

Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to +250°F (-40°C to +121°C)

PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.

Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

Compatibility & Interchange Data:

Snap-Tite 75-Series, Hydraulics Inc. Series- 5TV, DNP VFF-HD

Stucchi VOF, Faster OGV, Eaton FD85, Holmbury LC

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1 1/4"
Factory Part Number	10WSFP10
Material	Steel
Port	1 1/4"
Weight Lb	9.4000