

DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 04:52 AM

SKU

: 678

BRAND

: DIXON VALVE

MODEL

: 12EM12-B

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using solid brass

Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Steel sleeves are standard to maximize service life, hardened to resist deformation.

Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|---------------------------------|
| Body Size | 1-1/2" |
| Burst Pressure | 5,600 PSI (386 Bar) |
| Factory Part Number | 12EM12-B |
| Male Thread | NPTF |
| Male Thread Size | 1-1/2" - 11-1/2 |
| Material | Brass |
| Maximum Operating Pressure | 1,400 PSI (97 Bar) |
| Temperature Range | -40°F - +250°F (-40°C - +121°C) |
| Weight Lb | 2.8600 |