

WS-SERIES HIGH PRESSURE WINGSTYLE CODE 62 FLANGE HEAD COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 05:24 AM

SKU

: 22079

BRAND

: DIXON VALVE

MODEL

: 12WSFH12

Applications:

Used extensively in oil field and off shore oil rig applications

Features:

Interchanges with Snap-Tite 75 series

Contact Dixon ® for pressure ratings and other technical information

Construction:

Machined components are manufactured using solid steel bar stock.

Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Zinc Nickel for superior corrosion resistance.

Rugged high-strength steel wing nut for threaded connect and disconnect operation.

Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to +250°F (-40°C to +121°C)

PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.

Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

Compatibility & Interchange Data:

Snap-Tite 75-Series, Hydraulics Inc. Series- 5TV, DNP VFF-HD

Stucchi VOF, Faster OGV, Eaton FD85, Holmbury LC

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1 1/2"
Description	High Pressure Wingstyle Interchange Code 62 Flange Head Coupler
Factory Part Number	12WSFH12
Material	Steel
Port	1 1/2"
Weight Lb	11.4000