


**CAM & GROOVE ADAPTER  
BUTT WELD TO SCHEDULE 40  
PIPE/SOCKET WELD TO  
NOMINAL TUBING**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 11:17 AM

SKU  
: 1365

BRAND  
: DIXON VALVE

MODEL  
: 150AWBPSTAL

Applications:  
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:  
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Safety notes:  
Under no circumstances should cam and groove couplings be used for compressed air or steam service!  
Final weld preparation, as with all weld fittings, is the responsibility of the welder.

Line drawings are for reference only. Consult Dixon for specific dimensions.  
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard Buna-N seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Material</b>	356T6 Aluminum
<b>Maximum Operating Pressure</b>	250 PSI
<b>Factory Part Number</b>	150AWBPSTAL
<b>Size</b>	1-1/2"
<b>Weight Lb</b>	1.0000