

**DIXON® CAM & GROOVE  
COUPLER SOCKET WELD TO  
SCHEDULE 40 PIPE**

DATE  
: 07/09/2026 05:03 AM

SKU  
: 1381

BRAND  
: DIXON VALVE

MODEL  
: 150DWSPAL

Applications:  
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:  
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Available Options:  
Boss-Lock versions are also available. Consult Dixon for pricing and availability.

Safety notes:  
Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Final weld preparation, as with all weld fittings, is the responsibility of the welder.

Line drawings are for reference only. Consult Dixon for specific dimensions. Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Material</b>	356T6 Aluminum
<b>Maximum Operating Pressure</b>	250 PSI
<b>Factory Part Number</b>	150DWSPAL
<b>Size</b>	1-1/2"
<b>Weight Lb</b>	1.0000