


DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 01:38 AM

SKU
: 1776

BRAND
: DIXON VALVE

MODEL
: 16EF16-S

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Machined components are manufactured using 303 stainless steel bar stock. Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.

Nitrile (Buna-N) seals are standard

Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|---------------------------------|
| Body Size | 2" |
| Burst Pressure | 8,000 PSI (552 Bar) |
| Factory Part Number | 16EF16-S |
| Female Thread | NPTF |
| Female Thread Size | 2"-11-1/2 |
| Hex | 3-1/2" |
| Length | 3.00 (76.2mm) |
| Material | 303 Stainless Steel |
| Maximum OD | 3.83 (97.3mm) |
| Maximum Operating Pressure | 2,000 PSI (138 Bar) |
| Seal | Buna-N |
| Temperature Range | -40°F - +250°F (-40°C - +121°C) |
| Weight Lb | 1.6800 |