

DQC HT-SERIES FLUSHFACE FEMALE THREADED COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 11:58 AM

SKU

: 1778

BRAND

: DIXON VALVE

MODEL

: 16HTBF16

Specifications:

Rated pressure for connected Steel Coupler and Steel Plug: 3,000 PSI (207 bar) Maximum Working and 12,000 PSI (828 bar) burst

Rated pressure for uncoupled Steel Coupler: 3,000 PSI (207 bar) Maximum Working and 12,000 PSI (828 bar) burst

Features:

High flow performance, compact profile

Easily rebuildable!

DORS (dual opposing retention spheres) retention system prevents valve stem ejection during surge flow and pressure spike conditions.

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel coupler sleeves are hardened to resist deformation and maximize service life.

Couplers have polyurethane valve stem O-Ring, with a temperature range of -65° to +212°F

Ancillary coupler seals are Nitrile (Buna-N), with a temperature range of -40°F to +250°F

PTFE or TPC-ET Anti-Extrusion ring protects main coupling valve seal from dynamic impulse pressure damage.

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to ISO16028

Conforms to ISO16028 interchange standard interchangeable with Eaton/Hansen FF, Parker FEM, Snap-tite 74, Faster FFH/2FFN/2FFI, Stucchi A/FIRG and Holmbury HQ/A/FIMC

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	2"
Factory Part Number	16HTBF16
Hex	2-1/2"
Length	6.75"
Material	Steel
Maximum OD	3.95"
Pressure Rating	See Product Details
Thread	Female BSPP
Thread Size	2"-11
Weight Lb	13.8000