

REUSABLE FERRULE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/10/2026 12:50 PM

SKU

: 1923

BRAND

: DIXON VALVE

MODEL

: 1800611F

Applications:

Reusable fittings are recommended for low pressure air hose applications.

Use:

Recommended for use with rubber covered hose only

Features:

NOT for use in life dependency applications such as diving, for oxygen, air or other breathing applications. SEE WARNING TO THE RIGHT.

All re-usable fittings are of heavy duty construction.

They offer a more durable hose connection and are easily repaired.

Installation

Simply slip and twist ferrule on end of hose which has been trimmed flush. No skiving necessary.

Apply a drop or two of lubricant to fitting before inserting ferrule.

Turn reusable fitting into ferrule. Hose is expanded inside ferrule for perfect fit.

Note:

Caution: Check hose OD and ID accurately before ordering.

Safety notes:

Except as specifically noted as to a specific fitting, NO hose fittings manufactured and/or sold by any Dixon company can be safely used in life dependency applications such as diving, for oxygen, air, or other breathing applications. Our fittings are NOT designed and NOT recommended for such use and should NOT BE USED for that purpose. The use of non-approved hose fittings in such applications can result in death or grave personal injuries.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	1800611F
Weight Lb	0.0830
Hex	7/8"
Hose ID	3/8"
Hose OD	11/16"
Length	1.10"
Material	Brass
Maximum Operating Pressure	250 PSI at 70°F (21°C)