

## DQC H-SERIES ISO-B POPPET VALVE FEMALE THREADED COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 02:00 PM

SKU  
: 22217

BRAND  
: DIXON VALVE

MODEL  
: 1HF1

Features:  
Poppet style shut-off valves

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Steel componentry is plated using ROHS Compliant Trivalent Chrome.  
Steel coupler sleeves are hardened to resist deformation and maximize service life.  
Nitrile (Buna-N) seals are standard  
Redundant o-ring sealing system with PTFE backup ring

Available Options:  
Contact Dixon for all available option adders  
Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile, PTFE and Silicone  
Kalrez® seal options include: 4079, 6375 and 7075  
Valve options include: Unvalved, actuator, steel, brass, 303 stainless steel and 316 stainless steel  
Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged  
Oxy-clean treatment is available

Compatibility & Interchange Data:  
Meets dimensional requirements of ISO 7241 Series B  
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/8"
<b>Burst Pressure</b>	14500 PSI (1000 bar)
<b>Factory Part Number</b>	1HF1
<b>Hex</b>	9/16"
<b>Length</b>	1.90"
<b>Material</b>	Steel
<b>Maximum OD</b>	0.93"
<b>Maximum Operating Pressure</b>	4000 PSI (275 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1/8"-27
<b>Weight Lb</b>	0.1500