

DIXON® TYPE DD 90° ELBOW COUPLER X COUPLER

DATE
: 05/21/2026 06:27 PM

SKU
: 2195

BRAND
: DIXON VALVE

MODEL
: 200DD-90AL

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Construction:
Produced as a welded fabrication

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	200DD-90AL
Material	356T6 Aluminum
Maximum Operating Pressure	250 PSI
Seal	Buna-N
Size	2"
Weight Lb	1.9100