

**DIXON® CAM & GROOVE  
COUPLER BUTT WELD TO  
SCHEDULE 40 PIPE/SOCKET  
WELD TO NOMINAL TUBING**

DATE  
: 07/09/2026 05:04 AM

SKU  
: 2197

BRAND  
: DIXON VALVE

MODEL  
: 200DWPSTSS

Applications:  
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:  
Produced to interchange with all product produced to Commercial Item  
Description A-A-59326D

Available Options:  
Boss-Lock versions are also available. Consult Dixon for pricing and  
availability.

Safety notes:  
Under no circumstances should cam and groove couplings be used for  
compressed air or steam service!

Final weld preparation, as with all weld fittings, is the responsibility of the  
welder.

Line drawings are for reference only. Consult Dixon for specific dimensions.  
Pressure rating recommendations are based on the use of mating Dixon  
fittings at ambient temperature 70°F / 21°C with a standard seal installed. For  
use at elevated temperature or other unusual operating conditions, consult  
Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Material</b>	316 Stainless Steel
<b>Maximum Operating Pressure</b>	250 PSI
<b>Factory Part Number</b>	200DWPSTSS
<b>Size</b>	2"
<b>Weight Lb</b>	2.2800