

DIXON® CAM & GROOVE TYPE A ADAPTER X FEMALE NPT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 12:21 PM

SKU

: 2601

BRAND

: DIXON VALVE

MODEL

: 250-A-BR

Applications

Designed for use with liquids, consult Dixon for specific recommendations

Specifications:

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Features:

Precision machined to rigid tolerances

How it works

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down. Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service! Pressure rating is based on the seal of the mating part. Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon. WARNING: Cancer and Reproductive Harm-www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	250-A-BR
Material	Brass
Maximum Operating Pressure	150 PSI
Size	2-1/2"
Weight Lb	1.8200