

MALE NPTF SWIVEL X PUSH-ON HOSE BARB



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 03:42 AM

SKU
: 2729

BRAND
: DIXON VALVE

MODEL
: 2710404C

Specifications:
Number of Barbs: 2
Barb Length:.75"

Construction:
Dryseal

Installation

Assembly Instructions:

1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions

Disassembly instructions:

1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:

No hose clamps or ferrules are needed

Swivel is for assembly convenience only, not for live swivel applications

Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Caution: Push-on fittings will properly grip push-on hose only when pushed all

the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	2710404C
Component Material	Yellow Plastic Cap
Weight Lb	0.0610
Hex	9/16"
Hose ID	1/4"
Length	2.00"
Male Thread	NPTF
Male Thread Size	1/4"-18
Material	Brass
Pressure Rating	120 PSI
Temperature Rating	-40°F to 150°F