

MALE NPT X PUSH-ON HOSE BARB

DATE
: 07/10/2026 03:41 AM

SKU
: 2795

BRAND
: DIXON VALVE

MODEL
: 2721616C



Specifications:
Number of Barbs: 3
Barb Length: 1.50"

Construction:
Dryseal
Capped

Installation

Assembly Instructions:

1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions

Disassembly instructions:

1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:

No hose clamps or ferrules are needed

Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Caution: Push-on fittings will properly grip push-on hose only when pushed all

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|--------------------|
| Factory Part Number | 2721616C |
| Component Material | Yellow Plastic Cap |
| Weight Lb | 0.4940 |
| Hex | 1-3/8" |
| Hose ID | 1" |
| Length | 3.11" |
| Male Thread | NPTF |
| Male Thread Size | 1"-11-1/2 |
| Material | Brass |
| Pressure Rating | 350 PSI |
| Temperature Range | -40°F to 150°F |