

FEMALE NPTF X PUSH-ON HOSE BARB



DATE
: 07/08/2026 08:35 PM

SKU
: 2809

BRAND
: DIXON VALVE

MODEL
: 2740402CBC

Specifications:
Number of Barbs: 2
Barb Length:.77"

Construction:
Dryseal

Installation

Trim hose end with a smooth square cut.

Lubricate either Lok-On fitting, hose or both.

Insert Lok-on fitting into hose until first barb is in the hose.

Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

Note:

No hose clamps or ferrules are needed

Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	2740402CBC
Component Material	Brass Cap
Weight Lb	0.0280
Female Thread	NPTF
Female Thread Size	1/8"-27
Hex	1/2"
Hose ID	1/4"
Length	1.32"
Material	Brass
Pressure Rating	350 PSI
Temperature Range	-40°F to 150°F