

## FEMALE 45° SAE SWIVEL X PUSH-ON HOSE BARB



DATE  
: 05/21/2026 10:22 PM

SKU  
: 2885

BRAND  
: DIXON VALVE

MODEL  
: 2840610CBC

Specifications:  
Number of Barbs: 2  
Barb Length:.92"

Features:  
Notch in nut for SAE identification

### Installation

Trim hose end with a smooth square cut.

Lubricate either Lok-On fitting, hose or both.

Insert Lok-on fitting into hose until first barb is in the hose.

Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

### Note:

No hose clamps or ferrules are needed

### Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	2840610CBC
<b>Component Material</b>	Brass Cap
<b>Weight Lb</b>	0.0720
<b>Female Thread</b>	UNF
<b>Female Thread Size</b>	5/8"-18
<b>Hex</b>	3/4"
<b>Hose ID</b>	3/8"
<b>Length</b>	1.75"
<b>Material</b>	Brass
<b>Pressure Rating</b>	350 PSI
<b>Temperature Range</b>	-40 to +150°F
<b>Tube OD</b>	3/8"