

## FEMALE 37° JIC SWIVEL X PUSH-ON HOSE BARB



DATE  
: 07/08/2026 06:54 AM

SKU  
: 2921

BRAND  
: DIXON VALVE

MODEL  
: 2880409CBC

Specifications:  
Number of Barbs: 2  
Barb Length:.77"

#### Installation

Trim hose end with a smooth square cut.  
Lubricate either Lok-On fitting, hose or both.  
Insert Lok-on fitting into hose until first barb is in the hose.  
Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

#### Note:

No hose clamps or ferrules are needed

#### Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.  
Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

|                            |               |
|----------------------------|---------------|
| <b>Factory Part Number</b> | 2880409CBC    |
| <b>Component Material</b>  | Brass Cap     |
| <b>Weight Lb</b>           | 0.0530        |
| <b>Female Thread</b>       | UNF           |
| <b>Female Thread Size</b>  | 9/16"-18      |
| <b>Hex</b>                 | 11/16"        |
| <b>Hose ID</b>             | 1/4"          |
| <b>Length</b>              | 1.60"         |
| <b>Material</b>            | Brass         |
| <b>Pressure Rating</b>     | 350 PSI       |
| <b>Temperature Range</b>   | -40 to +150°F |
| <b>Tube OD</b>             | 3/8"          |