

**FEMALE 45° SAE SWIVEL X
PUSH-ON 90° ELBOW**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/21/2026 10:22 PM

SKU

: 2933

BRAND

: DIXON VALVE

MODEL

: 2890407CSAE

Specifications:

2 barbs

Features:

Notch in nut for SAE identification

Installation

Trim hose end with a smooth square cut.

Lubricate either Lok-On fitting, hose or both.

Insert Lok-on fitting into hose until first barb is in the hose.

Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

Note:

No hose clamps or ferrules are needed

Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	2890407CSAE
Component Material	Yellow Plastic Cap
Weight Lb	0.0620
Female Thread	UNF
Female Thread Size	7/16"-20
Hose ID	1/4"
Material	Plated Steel
Pressure Rating	350 PSI
Temperature Range	-40 to +150°F
Tube OD	1/4"