

**FEMALE 45° SAE SWIVEL X  
PUSH-ON 90° ELBOW**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 07:45 AM

SKU  
: 2935

BRAND  
: DIXON VALVE

MODEL  
: 2890610CSAE

Specifications:  
2 barbs

Features:  
Notch in nut for SAE identification

Installation  
Trim hose end with a smooth square cut.  
Lubricate either Lok-On fitting, hose or both.  
Insert Lok-on fitting into hose until first barb is in the hose.  
Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

Note:  
No hose clamps or ferrules are needed

Safety notes:  
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.  
Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	2890610CSAE
<b>Component Material</b>	Yellow Plastic Cap
<b>Weight Lb</b>	0.1100
<b>Female Thread</b>	UNF
<b>Female Thread Size</b>	5/8"-18
<b>Hose ID</b>	3/8"
<b>Material</b>	Plated Steel
<b>Pressure Rating</b>	350 PSI
<b>Temperature Range</b>	-40 to +150°F
<b>Tube OD</b>	3/8"