

**MALE SAE INVERTED FLARE
SWIVEL X PUSH-ON HOSE
BARB**



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 08:04 PM

SKU
: 2938

BRAND
: DIXON VALVE

MODEL
: 2900406C

Specifications:
Number of Barbs: 2
Barb Length:.77"

Installation
Assembly Instructions:
1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions
Disassembly instructions:
1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|--------------------|
| Factory Part Number | 2900406C |
| Component Material | Yellow Plastic Cap |
| Weight Lb | 0.0320 |
| Hex | 7/16" |
| Hose ID | 1/4" |
| Length | 1.52" |
| Male Thread | UNF |
| Male Thread Size | 3/8"-24 |
| Material | Brass |
| Pressure Rating | 350 PSI |
| Temperature Range | -40 to +150°F |
| Tube OD | 3/16" |