


## RIGID TUBE X PUSH-ON HOSE BARB



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/10/2026 06:05 PM

SKU

: 2977

BRAND

: DIXON VALVE

MODEL

: 2940808C

### Specifications:

Tube Length: 1.06"

Number of Barbs: 2

Barb Length: 1.02"

### Installation

#### Assembly Instructions:

1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

### Instructions

#### Disassembly instructions:

1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

### Note:

No hose clamps or ferrules are needed

### Safety notes:

Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

|                            |                    |
|----------------------------|--------------------|
| <b>Factory Part Number</b> | 2940808C           |
| <b>Component Material</b>  | Yellow Plastic Cap |
| <b>Weight Lb</b>           | 0.0590             |
| <b>Hose ID</b>             | 1/2"               |
| <b>Length</b>              | 2.13"              |
| <b>Material</b>            | Brass              |
| <b>Pressure Rating</b>     | 350 PSI            |
| <b>Temperature Range</b>   | -40 to +150°F      |
| <b>Tube OD</b>             | 1/2"               |