


**DQC CVV-SERIES EUROPEAN
INTERCHANGE FEMALE
COUPLER**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 10:49 PM

SKU
: 3052

BRAND
: DIXON VALVE

MODEL
: 2CVVFM1415

Construction:

Machined components are manufactured using solid bar stock

Steel retaining rings and springs maximize service life in rugged environments.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:

European Screw-Together Interchange

Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Note:

Threaded sleeves enable easy connection and disconnection while system is under residual pressure only.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	26000 PSI (1800 Bar)
Factory Part Number	2CVVFM1415
Hex	19mm
Length	2.33" (59.3mm)
Material	Steel
Maximum OD	1.34" (34.0mm)

TECHNICAL SPECIFICATIONS

Maximum Operating Pressure	6500 PSI (450 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female Metric
Thread Size	M14X1.5