


## DQC E-SERIES STRAIGHT THROUGH INTERCHANGE HOSE BARB COUPLER



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 03:39 AM

SKU

: 22269

BRAND

: DIXON VALVE

MODEL

: 2ES2-B

### Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings

These couplers have no internal valves, providing maximum flow with minimum pressure drop.

### Construction:

Machined components are manufactured using solid brass

Nitrile (Buna-N) seals are standard

### Available Options:

Contact Dixon® for additional seal material options, pressure ratings and other technical information.

### Safety notes:

Do Not Disconnect with pressure in line.

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Burst Pressure</b>	20,800 PSI (1,434 Bar)
<b>Factory Part Number</b>	2ES2-B
<b>Hose ID</b>	1/4"
<b>Length</b>	2.06" (52.2mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	1" (25.4mm)
<b>Maximum Operating Pressure</b>	5,200 PSI (359 Bar)
<b>Temperature Range</b>	-40°F - +250°F (-40°C - +121°C)
<b>Weight Lb</b>	0.1600