

L-SERIES LINCOLN PNEUMATIC FEMALE THREADED COUPLER



DATE
: 07/10/2026 06:57 PM

SKU
: 3109

BRAND
: DIXON VALVE

MODEL
: 2LF2-B

Construction:

Machined components are manufactured using solid bar stock.
Stainless steel springs. Carbon steel balls and retaining rings.
Nitrile (Buna-N) seals are standard
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Lincoln Long-Nose Automotive Interchange
Parker 70-Series, Tomco Series-1110, Coilhose Type-17

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	5000 PSI (345 bar)
Factory Part Number	2LF2-B
Hex	3/4"
Length	2.40"
Material	Brass
Maximum OD	0.90"

TECHNICAL SPECIFICATIONS

Maximum Operating Pressure	300 PSI (21 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	1/4"
Weight Lb	0.2500