

M-SERIES ARO PNEUMATIC AUTOMATIC MALE THREADED COUPLER



DATE
: 05/23/2026 09:40 PM

SKU
: 3114

BRAND
: DIXON VALVE

MODEL
: 2MM3-PL

Specifications:

Rated pressure for connected Steel Coupler & Steel Plug: 300 PSI (20 bar)
Maximum Working and 2,600 PSI (179 bar) Burst
Rated pressure for connected Steel Coupler & Brass Plug: 300 PSI (20 bar)
Maximum Working and 5,000 PSI (345 bar) Burst

Construction:

Machined components are manufactured using solid bar stock.
Stainless steel springs. Carbon steel balls and retaining rings.
Nitrile (Buna-N) seals are standard
Steel componentry is plated using ROHS Compliant Trivalent Chrome.


Compatibility & Interchange Data:

ARO 210
Hansen 210/310

Safety notes:

It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|--|
| Body Size | 1/4" |
| Factory Part Number | 2MM3-PL |
| Hex | 13/16" |
| Length | 1.80" |
| Material | Nickel Plated Brass Body, Steel Sleeve |
| Maximum OD | 1.06" |
| Pressure Rating | See Product Details |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | NPT |
| Thread Size | 3/8" |
| Weight Lb | 0.1800 |