

DIXON® CAM & GROOVE ADAPTER X 150# ANSI FLANGE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 03:25 AM

SKU
: 3205

BRAND
: DIXON VALVE

MODEL
: 300-AL-SSANSI

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Use:
Flanges are designed to mate with #150 ANSI flange

Specifications:
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

Construction:
Flange has raised face

How it works:
To make a connection, simply slide the adapter into the coupler and with
normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and
remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for
compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon
fittings at ambient temperature 70°F with a standard seal installed. For use at
elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	300-AL-SSANSI
Material	316 Stainless Steel
Maximum Operating Pressure	125 PSI
Size	3"
Thickness	15/16"
Weight Lb	10.8600