

## CAM & GROOVE ADAPTER X TTMA FLANGE

DATE  
: 07/08/2026 05:40 AM

SKU  
: 3206

BRAND  
: DIXON VALVE

MODEL  
: 300-ALT-AL

Applications:  
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:  
Produced to interchange with all product produced to Commercial Item  
Description A-A-59326D

Construction:  
Flange has flat face

How it works:  
To make a connection, simply slide the adapter into the coupler and with  
normal hand pressure, press the cam levers down.  
Uncoupling is as quick and simple as coupling. Just lift the cam arms and  
remove the adapter.

Safety notes:  
Under no circumstances should cam and groove couplings be used for  
compressed air or steam service!  
Pressure rating is based on the seal of the mating part  
Pressure rating recommendations are based on the use of mating Dixon  
fittings at ambient temperature 70°F (21°C) with a standard seal installed. For  
use at elevated temperature or other unusual operating conditions, consult  
Dixon.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Adapter Size</b>	3"
<b>Flange Size</b>	3"
<b>Material</b>	356T6 Aluminum
<b>Maximum Operating Pressure</b>	125 PSI
<b>Factory Part Number</b>	300-ALT-AL
<b>Weight Lb</b>	1.3000