

DIXON® TYPE DD 90° ELBOW COUPLER X COUPLER



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/21/2026 06:27 PM

SKU
: 3368

BRAND
: DIXON VALVE

MODEL
: 300DD-90SS

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

Construction:
Produced as a welded fabrication

How it works:
To make a connection, simply slide the adapter into the coupler and with
normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and
remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for
compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon
fittings at ambient temperature 70°F (21°C) with a standard seal installed. For
use at elevated temperature or other unusual operating conditions, consult
Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	300DD-90SS
Material	316 Stainless Steel
Maximum Operating Pressure	125 PSI
Seal	Buna-N
Size	3"
Weight Lb	12.1900