

**DIXON® CAM & GROOVE
COUPLER BUTT WELD TO
SCHEDULE 40 PIPE/SOCKET
WELD TO NOMINAL TUBING**

DATE
: 07/09/2026 05:04 AM

SKU
: 3370

BRAND
: DIXON VALVE

MODEL
: 300DWPSTSS

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item
Description A-A-59326D

Available Options:
Boss-Lock versions are also available. Consult Dixon for pricing and
availability.

Safety notes:
Under no circumstances should cam and groove couplings be used for
compressed air or steam service!

Final weld preparation, as with all weld fittings, is the responsibility of the
welder.

Line drawings are for reference only. Consult Dixon for specific dimensions.
Pressure rating recommendations are based on the use of mating Dixon
fittings at ambient temperature 70°F / 21°C with a standard seal installed. For
use at elevated temperature or other unusual operating conditions, consult
Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Material	316 Stainless Steel
Maximum Operating Pressure	125 PSI
Factory Part Number	300DWPSTSS
Size	3"
Weight Lb	3.5800