

BLOWER MOUNTED SWING CHECK VALVE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/25/2026 07:38 AM

SKU
: 3553

BRAND
: DIXON VALVE

MODEL
: 3090MB

Applications:

Designed specifically for use on tractor mounted air blowers and to replace the multiple pipe connections typically used to connect the blower to a swing check and air relief valve.

Use:

Fastens directly to blower using available TTMA thread adapters

Features:

Manufactured with a 4" TTMA flange connection for fastening directly to the blower

2" NPT port for air relief valve

Interchangeable inlet / outlet ports

Interchangeable inlet / outlet ports

Construction:

Aluminum body

White silicone spring loaded flapper

Stainless steel hardware

Silicone lid seal

Compact unit includes high flow swing check, port for air relief valve and inlet / outlet ports

All white silicone seals are compliant with FDA

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Component Material	White silicone flapper
Length	12-1/2"
Material	Aluminum
Maximum Temperature	400°F (204°C)
Outlet	4" Cam & Groove Adapter
Factory Part Number	3090MB
Weight Lb	7.5210