

BLOWER MOUNTED SWING CHECK VALVE



DATE
: 04/25/2026 07:39 AM

SKU
: 3560

BRAND
: DIXON VALVE

MODEL
: 3091MBS

Applications:

Designed specifically for use on tractor mounted air blowers and to replace the multiple pipe connections typically used to connect the blower to a swing check and air relief valve.

Use:

Fastens directly to blower using available TTMA thread adapters

Features:

Manufactured with a 4" TTMA flange connection for fastening directly to the blower

2" NPT port for air relief valve

Interchangeable inlet / outlet ports

Security kit installed

Construction:

Aluminum body

Metal spring loaded flapper

Stainless steel hardware

Silicone lid seal

Compact unit includes high flow swing check, port for air relief valve and inlet / outlet ports

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|-------------------------|
| Component Material | Metal flapper |
| Includes | Anti-tamper security |
| Length | 12-1/2" |
| Material | Aluminum |
| Maximum Temperature | 400°F (204°C) |
| Outlet | 4" Cam & Groove Adapter |
| Factory Part Number | 3091MBS |
| Weight Lb | 7.6000 |