

## METRIC PUSH-IN MALE CONNECTOR BSPP



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 11:13 PM

SKU

: 3566

BRAND

: DIXON VALVE

MODEL

: 31010613

Use:

Compatible tubing: semi-rigid nylon, polyurethane and polyethylene tube

Vacuum capability: vacuum of 28" Hg (99% vacuum)

Features:

Positive seal: sealing and holding is accomplished instantaneously

Reusable: connect and disconnect numerous times

Full flow: fitting seals on outside diameter of tubing

Internal hex allows ease of assembly in tight places

Construction:

Polypropylene release button

Nickel-plated brass threads

Silicone free

Installation

Quick connect and disconnect, no tools required

To connect, simply push tubing in.

To disconnect, press the release ring towards the fitting and pull tubing out.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                            |                               |
|----------------------------|-------------------------------|
| <b>Factory Part Number</b> | 31010613                      |
| <b>Male Thread</b>         | BSPP                          |
| <b>Male Thread Size</b>    | 1/4"                          |
| <b>Material</b>            | Nickel Plated Brass           |
| <b>Pressure Rating</b>     | 290 PSI at 70°F (21°C)        |
| <b>Seal</b>                | Buna-N D-seal                 |
| <b>Temperature Range</b>   | -4°F to 175°F (-20°C to 79°C) |
| <b>Tube OD</b>             | 6 mm                          |
| <b>Weight Lb</b>           | 0.0240                        |