

**LEGRIS D.O.T. PUSH-IN MALE
RUN TEE**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/23/2026 11:58 AM

SKU
: 3596

BRAND
: DIXON VALVE

MODEL
: 31035614DOT

Use:
Suitable fluids: compressed air only
Can be oriented 360° allowing proper positioning of the fitting

Specifications:
Complies with the performance requirements of D.O.T FMVSS 571.106 (SAE J1131) and SAE J2494-3
Meets D.O.T. FMVSS 571.106, SAE J1131 and SAE J2494-3

Construction:
Composite body, brass collet, stainless steel tube support and brass threads

Safety notes:
Designed for use on all pneumatic circuits other than air brake assemblies between the frame and axle or between towed and towing vehicle
Pressure rating given at ambient temperature 70°F/21°C
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	31035614DOT
Male Thread	NPT
Male Thread Size	1/4"
Material	Composite/Brass
Maximum Operating Pressure	250 PSI
Seal	Buna-N
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Tube OD	1/4"

TECHNICAL SPECIFICATIONS

Weight Lb	0.0800
------------------	--------