

**LEGRIS D.O.T. PUSH-IN MALE ELBOW**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/10/2026 09:32 PM

SKU  
: 3702

BRAND  
: DIXON VALVE

MODEL  
: 31096014DOT

Use:

Suitable fluids: compressed air only

Can be oriented 360° allowing proper positioning of the fitting

Specifications:

Complies with the performance requirements of D.O.T FMVSS 571.106 (SAE J1131) and SAE J2494-3

Meets D.O.T. FMVSS 571.106, SAE J1131 and SAE J2494-3

Construction:

Composite body, brass collet, stainless steel tube support and brass threads

Safety notes:

Designed for use on all pneumatic circuits other than air brake assemblies between the frame and axle or between towed and towing vehicle

Pressure rating given at ambient temperature 70°F/21°C

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	31096014DOT
<b>Male Thread</b>	NPT
<b>Male Thread Size</b>	1/4"
<b>Material</b>	Composite/Brass
<b>Maximum Operating Pressure</b>	250 PSI
<b>Seal</b>	Buna-N
<b>Temperature Range</b>	-40°F to 200°F (-40°C to 93°C)
<b>Tube OD</b>	3/8"

**TECHNICAL SPECIFICATIONS**

<b>Weight Lb</b>	0.1040
------------------	--------