

LEGRIS D.O.T. PUSH-IN MALE ELBOW



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 09:33 PM

SKU
: 3710

BRAND
: DIXON VALVE

MODEL
: 31096218DOT

Use:

Suitable fluids: compressed air only

Can be oriented 360° allowing proper positioning of the fitting

Specifications:

Complies with the performance requirements of D.O.T FMVSS 571.106 (SAE J1131) and SAE J2494-3

Meets D.O.T. FMVSS 571.106, SAE J1131 and SAE J2494-3

Construction:

Composite body, brass collet, stainless steel tube support and brass threads

Safety notes:

Designed for use on all pneumatic circuits other than air brake assemblies between the frame and axle or between towed and towing vehicle

Pressure rating given at ambient temperature 70°F/21°C

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	31096218DOT
Male Thread	NPT
Male Thread Size	3/8"
Material	Composite/Brass
Maximum Operating Pressure	250 PSI
Seal	Buna-N
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Tube OD	1/2"

TECHNICAL SPECIFICATIONS

Weight Lb	0.1600
------------------	--------