

LEGRIS D.O.T. PUSH-IN FEMALE CONNECTOR



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/10/2026 07:49 PM

SKU
: 3718

BRAND
: DIXON VALVE

MODEL
: 31140411DOT

Use:
Suitable fluids: compressed air only

Specifications:
Complies with the performance requirements of D.O.T FMVSS 571.106 (SAE J1131) and SAE J2494-3
Meets D.O.T. FMVSS 571.106, SAE J2494 and SAE J2494-3

Construction:
Composite body, brass collet, stainless steel tube support and brass threads

Safety notes:
Designed for use on all pneumatic circuits other than air brake assemblies between the frame and axle or between towed and towing vehicle
Pressure rating given at ambient temperature 70°F/21°C
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|--------------------------------|
| Factory Part Number | 31140411DOT |
| Female Thread | NPT |
| Female Thread Size | 1/8" |
| Material | Composite/Brass |
| Maximum Operating Pressure | 250 PSI |
| Seal | Buna-N |
| Temperature Range | -40°F to 200°F (-40°C to 93°C) |
| Tube OD | 5/32" |

TECHNICAL SPECIFICATIONS

| | |
|------------------|--------|
| Weight Lb | 0.0200 |
|------------------|--------|