

LEGRIS NYLON PUSH-IN TUBE WYE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/11/2026 12:18 AM

SKU
: 3770

BRAND
: DIXON VALVE

MODEL
: 31400800

Use:

Compatible tubing: semi-rigid nylon, polyurethane and polyethylene tube
Vacuum capability: vacuum of 28" Hg (99% vacuum)

Features:

Positive seal: sealing and holding is accomplished instantaneously
Reusable: connect and disconnect numerous times
Full flow: fitting seals on outside diameter of tubing

Construction:

Black body is glass-filled nylon
Buna-N D seal
Polypropylene release button
Silicone free

Installation

Quick connect and disconnect, no tools required.
To connect, simply push tubing in.
To disconnect, press the release ring towards the fitting and pull tubing out.

Safety notes:

Maximum circuit pressure depends equally on the type and diameter of the tube used.

Pressure rating given at ambient temperature 70°F/21°C.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	31400800
Material	Nylon
Seal	Buna-N D seal
Temperature Range	-4°F to 175°F (-20°C to 79°C)
Tube OD	5/16"
Weight Lb	0.0100
Working Pressure	290 PSI at ambient temperature