

**LEGRIS D.O.T. PUSH-IN Y UNION**

DATE  
: 05/23/2026 12:39 PM

SKU  
: 3773

BRAND  
: DIXON VALVE

MODEL  
: 31405600DOT

Use:  
Suitable fluids: compressed air only

Specifications:  
Complies with the performance requirements of D.O.T FMVSS 571.106 (SAE J1131) and SAE J2494-3

Construction:  
Composite body, brass collet, stainless steel tube support

Safety notes:  
Designed for use on all pneumatic circuits other than air brake assemblies between the frame and axle or between towed and towing vehicle  
Pressure rating given at ambient temperature 70°F/21°C  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	31405600DOT
<b>Material</b>	Composite/Brass
<b>Maximum Operating Pressure</b>	250 PSI
<b>Seal</b>	Buna-N
<b>Temperature Range</b>	-40°F to 200°F (-40°C to 93°C)
<b>Tube OD</b>	1/4"
<b>Weight Lb</b>	0.0360



\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability