


SWIVEL JOINT STYLE 30 FEMALE NPT X FEMALE NPT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/12/2026 12:04 AM

SKU

: 27045

BRAND

: DIXON VALVE

MODEL

: 330FXFOC00000

Applications:

Used wherever a leak-proof swivel connection is needed in pipelines or in combination with hoses to eliminate hose twisting

Industries range from petroleum, petrochemical, refining, mining, distilling, paint, farm irrigation and fertilizing, wastewater treatment plants and food and beverage process equipment. Dixon™'s swivel joints are found in blending plants, drum filling applications, fluid and dry bulk transfer, vacuum trucks, oil and gas trucks and water trucks. Larger swivels can be found in the steel industry, marine bulk transfer and many more.

Features:

O-ring pressure seal ensures a leak-proof seal and smooth rotation with lower torque.

Full 360° rotational movement

Wide spacing between dual ball bearing raceways ensures greater load bearing capacity

Precision-machined design ensures alignment and years of trouble-free service

Hydrostatic testing is performed on all swivels before shipment

O-ring dust seal protects the ball races and seals chamber from outside elements

Available Options:

End configurations: female NPT, #150 flange, TTMA flange, grooved, weld end and many other variations

Seal options: Buna, FKM, PTFE, EPDM, FDA Buna, FFKM

Ball bearing materials: carbon steel, 440 stainless steel and 316 stainless steel

Grease materials: Lithium, FDA approved/food grade and silicone

Swivels that include oxygen, steam or submerged service can be specifically designed for unique applications (special order)

100% full penetration welding available

Note:

Custom swivel options available, contact Dixon™ for information. Our factory sales and engineering staff will be happy to help you evaluate your swivel application and determine the proper swivel joint needed. Please call 800.355.1991.

Re-build kits available

Safety notes:

The Swivel should be packed such that the surfaces coming in contact with the fluid being handled are compatible with that fluid. In case of the use of the swivel in submerged service, this would include the dust seals and ball bearings. We always recommend the use of the stainless steel ball bearings when building a swivel for submerged service, since should the standard carbon steel ball bearings rust together, they make it possible to disassemble the swivel and may affect operation.

Lubrication should be performed periodically, depending on service and operating conditions. Twice yearly is normally sufficient.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Ball Bearings	Carbon Steel
Dust Seal	Buna-N
Grease	Standard
Material	Carbon Steel
Factory Part Number	330FXFOC00000
Pressure Seal	Buna-N
Retainer	No Retainers
Size	3"
Style	O-Ring
Weight Lb	15.0000