

STEEL 3500 NIPPLE WITH FERRULE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/24/2026 12:22 PM

SKU

: 22396

BRAND

: DIXON VALVE

MODEL

: 3514WF

Use:

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.

To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.

Features:

Low profile

Streamline appearance

Construction:

Zinc plated steel 3500 nipple

Carbon steel ferrule

Installation

Can be crimped or swaged-on to achieve maximum coupling sealing and retention

Note:

For crimp or swage recommendations, contact Dixon.

Safety notes:

For air and water service only

To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose.

TECHNICAL SPECIFICATIONS

Factory Part Number	3514WF
Hose OD From	1-10/64"
Hose OD To	1-14/64"
Hose Size	3/4"
Male Thread	NPT
Male Thread Size	3/4"
Material	Steel
Pressure Rating	600 PSI at 70°F (21°C)
Weight Lb	0.6400