

**STEEL 3500 MALE NIPPLE**



DATE  
: 05/24/2026 12:17 PM

SKU  
: 22398

BRAND  
: DIXON VALVE

MODEL  
: 3516

Use:

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.

To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.

Safety notes:

For air and water service only

To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	3516
<b>Hose Size</b>	1"
<b>Male Thread</b>	NPT
<b>Male Thread Size</b>	3/4"
<b>Material</b>	Zinc Plated Steel
<b>Pressure Rating</b>	600 PSI at 70°F (21°C)
<b>Weight Lb</b>	0.8000