

## STEEL 3500 FEMALE NIPPLE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/24/2026 11:14 AM

SKU  
: 22404

BRAND  
: DIXON VALVE

MODEL  
: 3546

**Use:**

The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.

To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.

**Safety notes:**

For air and water service only

To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	3546
<b>Female Thread</b>	NPT
<b>Female Thread Size</b>	3/8"
<b>Hose Size</b>	3/8"
<b>Material</b>	Zinc Plated Steel
<b>Pressure Rating</b>	600 PSI at 70°F (21°C)
<b>Weight Lb</b>	0.1250