

## NICKEL-PLATED BRASS LEGRIS PUSH-IN EQUAL UNION



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/24/2026 12:58 AM

SKU  
: 3883

BRAND  
: DIXON VALVE

MODEL  
: 36066200

### Applications:

Applications include: food industry, packaging, robotics, pulp and paper and wash down

Push-to-connect forged fittings are nickel plated and have an FKM seal making them suitable to use with liquids and gaseous fluids. Fittings are plated with a high phosphorous FDA nickel plate allowing them to be used in applications where exposure to harsh environments is present.

### Features:

Full flow  
Excellent resistance to abrasion and corrosion  
Silicone free

### Construction:

Body: High phosphorous FDA nickel plated brass  
Back-up washer: High phosphorous FDA nickel plated brass  
Collet: High phosphorous FDA nickel plated brass  
O-ring: FKM fluoroelastomer conforming to FDA standards  
Base: High phosphorous FDA nickel plated brass

### Available Options:

Available in fractional and metric sizes, contact Dixon™ for more information

### Safety notes:

Maximum circuit pressure depends on media, temperature and diameter of tube used

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	36066200
<b>Material</b>	Nickel-Plated Brass
<b>Maximum Operating Pressure</b>	435 PSI
<b>Seal</b>	FKM
<b>Temperature Range</b>	-4°F to 302°F (-20°C to 150°C)
<b>Tube OD</b>	1/2"
<b>Vacuum Capability</b>	28" HG
<b>Weight Lb</b>	0.0950