

LEGRIS STAINLESS STEEL PUSH-IN UNION TEE



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/23/2026 09:42 PM

SKU
: 3987

BRAND
: DIXON VALVE

MODEL
: 38046200

Applications:
Suitable for many industries such as: chemical, food, packaging and medical

Use:
Compatible with a range of tubes including: semi-rigid nylon tube, flexible polyurethane tube, low density polyethylene, PTFE tube FEP 140, stainless steel and copper tube (when grooved)

Specifications:
Materials conforming to FDA and 1934/2004 CE standards

Construction:
AISI 316 stainless steel body with 316L stainless steel backup washer and 303L stainless steel collet
Silicone free
FKM O-ring

Safety notes:
Maximum circuit pressure depends equally on the type and diameter of the tube used.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	38046200
Material	Stainless Steel
Maximum Operating Pressure	290 PSI
Seal	FKM O-ring
Temperature Range	-4°F to 245°F (-20°C to 118°C)
Tube OD	1/2"
Vacuum Capability	28" HG
Weight Lb	0.1450