

LEGRIS STAINLESS STEEL PUSH-IN MALE CONNECTOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 08:45 PM

SKU

: 3993

BRAND

: DIXON VALVE

MODEL

: 38056222

Applications:

Suitable for many industries such as: chemical, food, packaging and medical

Use:

Compatible with a range of tubes including: semi-rigid nylon tube, flexible polyurethane tube, low density polyethylene, PTFE tube FEP 140, stainless steel and copper tube (when grooved)

Specifications:

Materials conforming to FDA and 1934/2004 CE standards

Features:

Internal hex allows ease of assembly in tight places

Construction:

AISI 316 stainless steel body with 316L stainless steel backup washer and 303L stainless steel collet

Silicone free

FKM O-ring

Note:

Thread sealant does not come pre-applied on male threads, allowing the appropriate sealant for the application to be applied by the user.

Safety notes:

Maximum circuit pressure depends equally on the type and diameter of the tube used.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	38056222
Male Thread	NPT
Male Thread Size	1/2"
Material	Stainless Steel
Maximum Operating Pressure	290 PSI
Seal	FKM O-ring
Temperature Range	-4°F to 245°F (-20°C to 118°C)
Tube OD	1/2"
Vacuum Capability	28" HG
Weight Lb	0.1000