

## LEGRIS STAINLESS STEEL PUSH-IN MALE ELBOW



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 08:45 PM

SKU

: 4002

BRAND

: DIXON VALVE

MODEL

: 38895614

Applications:

Suitable for many industries such as: chemical, food, packaging and medical

Use:

Compatible with a range of tubes including: semi-rigid nylon tube, flexible polyurethane tube, low density polyethylene, PTFE tube FEP 140, stainless steel and copper tube (when grooved)

Specifications:

Materials conforming to FDA and 1934/2004 CE standards

Features:

The body is orientable for positioning purposes.

Construction:

AISI 316 stainless steel body with 316L stainless steel backup washer and 303L stainless steel collet

Silicone free

FKM O-ring

Note:

Thread sealant does not come pre-applied on male threads, allowing the appropriate sealant for the application to be applied by the user.

Safety notes:

Maximum circuit pressure depends equally on the type and diameter of the tube used.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                                   |                                |
|-----------------------------------|--------------------------------|
| <b>Factory Part Number</b>        | 38895614                       |
| <b>Male Thread</b>                | NPT                            |
| <b>Male Thread Size</b>           | 1/4"                           |
| <b>Material</b>                   | Stainless Steel                |
| <b>Maximum Operating Pressure</b> | 290 PSI                        |
| <b>Seal</b>                       | FKM O-ring                     |
| <b>Temperature Range</b>          | -4°F to 245°F (-20°C to 118°C) |
| <b>Tube OD</b>                    | 1/4"                           |
| <b>Vacuum Capability</b>          | 28" HG                         |
| <b>Weight Lb</b>                  | 0.0500                         |